

Technische gegevens


Luchtdebiet [m3/h]	1138
Druk [Pa]	260.9
Druktype	Psta
Voeding	all
Dichtheid [kg/m3]	1.205

Typeplaatgegevens

Code	TCV314
Spanning [V]	400
Fasen	3
Stroom [A]	0.84
Polen	4
Gewicht [kg]	26
Frequentie [Hz]	50
Toerental [rpm]	1450
Vermogen [kW]	0.25
IP	55
Isolatieklasse	

Motorgegevens

IE-klasse	IE2
Grootte	71
Vermogen [kW]	0.25
Stroom [A]	0.84
Spanning [V]	400
Cos ϕ	0.72
n (rendement)	0.6








- PE gegoten huis
- PP gegoten waaier
- Roestvrijstalen schroeven

Certificeringen




Werkpunt

Q [m ³ /h]	1138
P _{sta} [Pa]	260.9
P _{tot} [Pa]	265.0
P _{in} [W]	108.3
n _{sta}	0.762
n _{tot}	0.773
Toerental [rpm]	1450




Afmetingen



A	B	C	D	E	F	I	L	M	N	N°	O
600	560	240	280	600	50	325	365	540	80	8	490

Configuraties & CAD

LG 0°



Accessoires

Bocht 90°
280mm



Deflectorkap
280mm



Flexibele verbinding
280mm



Geluidsdemper
280/400mm



Zelfsluitende klep
280mm



Handbediende regelklep
280mm



Vaste verloop
160/280mm



Vaste verloop
180/280mm



Vaste verloop
200/280mm



Vaste verloop
225/280mm



Vaste verloop
250/280mm



Vaste verloop
280/315mm





Accessoires

Vaste verloop
280/355mm



Vaste verloop
280/400mm



Vaste verloop
280/450mm



Vaste verloop
280/500mm



Vaste verloop
80mm



Uitblaaskap met gaasrooster
280mm

